

FIELD NOTES

T. 1 S., R. 14 W., S. B. M.

N. B. Sections 3, 4, 5, 9
 W. B. " 3, 4, 9, 10

Copied from Notes loaned by S. B. Reeve.

	R. 14 W.						
T. 1 N.	31	32	33	34	35	36	T. 1 N.
T. 15.	6	5	4	3	2	1	T. 15.
	7	8	9	10	11	12	
	18	17	16	15			

W. P. Reynolds 1878

NORTH BOUNDARY.

WEST on SOUTH BOUNDARY of Section 35, T. 1 N., R. 14 W.
Var. 15° 05' E.

80.00 Set a sand rock 20 x 14 x 10 ins. 10 ins. deep and raised mound of sand rock 30 ins. high 3 ft. base for corner to sections 34 & 35. Land broken and hilly with thick scrub and chaparral oak. Soil 3rd rate.

WEST on SOUTH BOUNDARY of Section 34. Var. 15° 05' E.

6.00 Cross dry ravine 20 lks. wide course N. 60° W.
19.50 Cross dry ravine 20 lks. wide brs. S. 30° W. and ascend hill. House of Evers brs. S. 10° E. about 10.00 chs. dist.
22.50 Top of ascent ridge brs. N. & S. and descend.
27.00 Foot of descent cross wash 10 lks. wide, ascend.
38.00 Top of ascent high ridge brs. N. & S. and descend.
40.00 Set $\frac{1}{4}$ section rock 7 x 9 x 15 ins. 6 ins. deep in mound of rock 30 ins. sq. at the base and 24 ins. high. From which the House of John Donaldson brs. S. 10° W. dist. 16.00 chs.
42.50 Foot of descent, cross gulch 10 lks. wide course S. ascend S. slope of hill.
48.00 Top of ascent ridge brs. S. and descend.
53.00 Foot of descent cross road in Cahuenga pass bearing N. 40° W. and S. 40° E.
54.00 Cross Cahuenga pass and ascend steep brush and broken hills.
57.00 Top of ascent, ridge brs. N. 65° W. and S. 65° E. thence along its southerly slope, descend.
67.00 Foot of descent, across ravine 2 lks. wide, course S. 65° E. ascend along northerly slope of ridge.
75.00 Top of ascent, ridge brs. N. 65° W. and S. 65° E. Finding it would be impracticable to set corner at 80 00 chs. I set a witness corner.
76.00 On the brow of summit and marked sandstone rock 18 x 20 x 24 ins. and constructed mound of stone 3 ft. sq. 24 ins. high for witness corner to sections 33 and 34, and run along the steep south slope of ridge.
80.00 True point for corner to sections 33 & 34. Find it impossible to build corner at this point. Land broken and hilly, soil 3rd rate.

WEST on SOUTH BOUNDARY of Section 33 from true corner. Var. 15° 05' E.

5.00 Foot of descent across ravine 50 lks. wide brs. S. 65° E. Ascend.
12.00 Top of ascent, ridge brs. NW. & SE. descend.
18.00 Foot of descent and in valley, course SE.
36.00 Leave valley and ascend.
38.00 Top of ridge enter low gap brs. N. & S. descend.
40.00 Raised mound of stone for $\frac{1}{4}$ section corner, 3 ft. sq. 20 ins. high. Var. 14° 45' E.
46.00 Foot of descent and run along N. face of ridge.
62.00 To deep ravine 60 lks. wide, course S. Ascend.
67.00 Top of ascent, ridge brs. E. & W. run along same.
71.00 Leave top of ridge descend across south slope.
80.00 Raised mound of rock for corner to sections 32, 33, 3 ft. sq. 30 ins. high. Land broken and hilly. Soil 2nd rate.

WEST on SOUTH BOUNDARY of Section 32.

Var. 14° 55' E.

- 10.00 Foot of descent across ravine 50 lks. wide course SE. ascend.
15.00 Top of ascent, ridge brs. SE. descend.
18.00 Foot of descent across ravine 40 lks. wide course S. 60° E. ascend.
26.00 Top of ascent, ridge brs. S. 80° E. descend.
30.00 Foot of descent, ravine brs. S. 65° E. 60 lks. wide, ascend.
36.00 Top of ascent, ridge brs. S. 65° E.
39.00 Descend.
40.00 Raised mound of stone 30 ins. sq. 20 ins. high for $\frac{1}{4}$ section corner.
47.00 Foot of descent cross ravine 60 lks. wide brs. S. 70° E. ascend.
60.00 Top of ascent, ridge brs. NW. & SE., descend.
72.00 Foot of descent cross ravine 70 lks. wide, course S. ascend.
Steep hill.
80.00 Raised mound of sand rock 3 ft. base 30 ins. high for corner to sections 31, 32.
Land very broken and mountainous. Soil 3rd rate. (W.F.Reynolds 1878)

SUBDIVISIONS

NORTH between sections 9 & 10.

Var. 14° 30' E.

- 80.00 Set sandstone 22 x 20 x 18 ins. 14 ins. in the ground marked as per instructions for corner to sections 3, 4, 9 & 10.
From which the center of
 Thomas Urgudez house brs. due E. 65 lks. dist.
 Large Sycamore 3 ft. dia. brs. due W. 57 lks. dist.
Land for first 40 chs. level. Soil 1st class.
Last 40 chs. land gently rising, soil gravelly 2nd rate.

NORTH between sections 3 & 4.

Var. 14° 30' E.

- 6.00 To base of hill, steep range from which it is impossible to measure. Set Redwood post and charred stake in mound with pits as per instructions.

February 8, 1871

NORTH between sections 8 & 9.

- 8.00 To road, course E. & W. gradually ascend.
23.00 Enter underbrush, course E. & W.
40.00 Set $\frac{1}{4}$ section post and charred stake in mound with pits as per instructions.
57.82 To road, course E. & W.
59.00 Leave undergrowth and commence ascending steep range.
72.60 To top of spur, course SE.
80.00 Set sandstone 25 x 16 x 10 ins. 12 ins. in the ground and marked as per instructions for corner to sections 4, 5, 8 & 9.
Land for first 20 chs. gentle ascent. Soil 1st rate.
Next 40 chs. thru Chemical, undergrowth and low castus with a few scattering clumps of Sumac and wild cherry. Soil 2nd rate.
Next 20 chs. up the side of a steep barren mountain.

EAST on a RANDOM line between sections 4 & 9. Var. 14° 30' E.

Find it impossible to run a random line East I offset 22.00 chs. S. to a point, thence EAST on offset line. Var. 14° 30' E.

- 16.00 To mouth of Canada de los Alisos ranging N. 10° E. 6 chs. wide at mouth.

20.00 To Nicholas' house 5 chs. N. of line
 40.00 Set post for temporary $\frac{1}{4}$ section corner.
 50.00 Intersect the line between sections 9 & 10 and run N. 22 chs. (to a point) 9 lks. N. of corner to sections 3, 4, 9 & 10. From which corner I run

N. 89° 56' W. on a TRUE line.

Var. 14° 30' E.

.50 Cross Zanja 5 lks. wide, course SE.
 2.00 To dry wash 50 lks. wide, course S.
 10.00 To E. base of S. spur of abrupt range over which it was impossible to measure.
 I set a Redwood post and stake in mound with pits as per instructions.

From which a

Scrub Oak 3 in. dia. brs. S. 46° E. 67 lks.

Return to the random offset line where it intersects the line between sections 9 & 10 and run N. 89° 56' W.

40.00 Thence N. 22.04 (21.91) chs. to $\frac{1}{4}$ section corner between sections 4 & 9.

Var. 14° 30' E.

50.00 Meet S. base of high range at 10 chs. N. of temporary corner. The corner to sections 4, 5, 8 & 9. Land Mountainous. Soil 2nd rate.

John Goldsworthy
 1871

(See below for this line)

Commence at the corner to sections 3, 4, 9 & 10. NORTH between sections 3 & 4.

6.00 Find mound of rock, ascend.
 15.00 Top of ascent and over broken ground.
 17.00 Descend.
 22.00 Foot of descent and ascend.
 30.00 Top of ascent.
 31.00 Descend.
 35.00 Foot of descent and in ravine running S.
 40.00 Set large Hornblende rock 8 x 8 x 24 ins. 12 ins. in ground, placed 4 other large rocks around the first rock set for $\frac{1}{4}$ section corner.
 45.00 Cross ravine 1 ch. wide course S. thence along right bank of same.
 50.00 Cross ravine (same) 1 ch. wide, course S. 60° E. ascend.
 55.00 Descend.
 62.00 Foot of descent to ravine 50 lks. wide brs. S. 65° E. ascend.
 72.00 Top of ascent and ridge brs. S. 65° E. descend.
 76.00 Foot of descent cross ravine 20 lks. wide, course S. 65° E.
 80.12 Intersect the base line 22 lks. E. of true corner to T. 1 N., R. 14 W., Sections 33 & 34 and 3 chs. 78 lks. W. of witness corner established on base line of secs. 33 & 34. Land very broken covered with thick chaparral.

Commence at the corner to Secs. 4, 5, 8 & 9. EAST between sections 4 & 9 on RANDOM line.

Var. 15° 10' E.

40.00 Set temporary $\frac{1}{4}$ section corner.
 70.00 Intersect the La Brea Rancho line.
 80.00 Intersect at the established cor. to secs. 3, 4, 9 & 10.

WEST on a TRUE line between secs. 4 & 9.

Var. 15° 10' E.

- 10.00 To stake & mound La Brea R. Station No. 15.
40.00 Set rock 10 x 12 x 16 in. in rock mound 3 ft. sq. 20 in. high for
¼ sec. cor.
80.00 Corner to secs. 4, 5, 8 & 9.
Land broken hills. Brush and Chaparral. (See page 2 above)
-

NORTH between secs. 4 & 5.

Var. 15° 10' E.

- 18.00 Foot of descent cross ravine 20 lks. wide, course W. ascend.
27.00 Top of ascent, ridge brs. S. 80° E. descend.
37.00 Foot of descent in canyon 50 lks. wide, course S. 50° W.
40.00 Set large sandstone 8 x 10 x 30 ins. for ¼ sec. cor. and raised
mound of rock 3 ft. dia. at base 20 ins. high.
42.00 Leave canada ascend E. slope of hill.
53.00 To canyon and in same course S. 55° E.
62.00 Leave same and ascend.
69.00 Top of ascent, ridge brs. E. & N. descend.
74.00 Foot of descent.
75.50 Cross dry ravine 20 lks. wide, course S. 65° E.
80.10 Intersect the Base Line at established cor. to T. 1 N., R. 14 W.,
Secs. 32 and 33. Land very broken, rising mts. covered with
dense chaparral.

W. P. Reynolds
1878
